

## Ultra360° LPG/CNG Filter

A brand new, improved filter with oil separation; effective filtration combined with ergonomics



The original construction of the filter ensures very effective filtration. Gas entering the filter is set in rotary motion and directed towards the bottom. Thanks to the rotary motion, centrifugal force and inertial force, particular and liquid matters are centrifuged and kept on the bottom. Additionally, the filter cartridge cleans the stream of gas heading upwards from the remaining tiny impurities.

Ultra 360° was designed especially for the convenience of the installers. The inlet and outlet are placed on separate elements of filter cover, which results in easy angle regulation between them. Because of such solution the installer can easily and freely place the filter in the underbonnet area.

Code	GF1212	GF1222	GF1612	GF1622
Input diameter [mm]	Ø12		Ø16	
Output diameter [mm]	Ø12			
Number of outputs	1	2	1	2
Filter's height [mm]	106		110	
Homologation	E8 67R-017075; E8 110R-007076			

### TECHNICAL SPECIFICATION

- Cover material: polyamide and glass composite
- Filtrating material: polyester
- Classification: CLASS#2
- Classifying pressure: 4,5 bar
- Working temperature

Filter Ultra 360°



### DIMENSIONS:

60 x 60 x 110 (with nozzles set at 180° degrees)